2024/11 アモンド 1/2

株式会社 森傳生地品質検査報告書

商品名 アモンド Amondo

種類	織物	ф	137	cm	巻数	50	m乱	
組成	ポリエ	ステル1	.00%					

																									1						
	耐光	摩	摩擦 JIS L 0849 II型		汗				耐光	摩擦				汗 IIS L 0848		— 色名	耐光 JIS L 0842	JIS L 084	擦		汗				耐光	摩擦 JIS L 0849 II 型			;	汗	
色名 JIS L C	JIS L 0842				JIS L 0848			色名	JIS L 0842	JIS L 0849 II 型													L 0848		JIS L 0842					. 0848	
	-		100往復		汚染		トカリ 汚染			30回/分			酸		カリ 汚染			30回/分 100往復		酸		アルカリ				30回/分 100往復		酸汚染		アルカリ	
		乾燥	湿潤	変退色	綿/絹	変退色	綿/絹			乾燥	湿潤	変退色	綿/絹	変退色	綿/絹			乾燥	乾燥 湿潤	変退色	綿/絹	変退色	綿/絹			乾燥	湿潤	変退色	綿/絹	変退色	綿/
w	4以上	5	5																												
ı	4以上	5	5																												
CA	4以上	5	5																												
BR	4	5	5																									***********	•••••		
DBR	4以上	5	5																												
CGR	3-4	5	5																							***************************************				************	
BL	4以上	4-5	4-5																									************			
****				·······			·K																								
L																		ı			ı				1						
11252/	(1)	41	÷ (2.1)					滑脱	抵抗力		## == -:						76.1			ピリン	スナッグ (級)					寸法変化率 (%)					
張強 a	ž (N)	伸び	率 (%)	引裂強さ(N)					ım)		縫目強	iさ (N)				摩耗	強さ			グ(級)				涉		ドライ				布目曲力	布目曲がり(%

株式会社 森傳生地品質検査報告書

商品名 アモンド Amondo

種類 織物 巾 137 cm 巻数 50 m乱 組成 ポリエステル100%

	染色堅牢度(級)																														
	洗濯 ドライクリーニング																														
色名	JIS L A法		JIS L 0860 A-1法																												
	変退色	汚染	変退色	汚染																											
		綿/絹				1		1	1	1											1	1							1		
DBR	4-5	4-5/5	5	5																										ļ	ļ
																														j	
								<b></b>																				······		<u> </u>	h
						ļ		<b></b>																				<b> </b>	ļ	<u> </u>	
							<b>,</b> ,,,,,,,,,,		········																						ļ
																														<u> </u>	<u> </u>
																														]	
																														ļ	
					<u> </u>																										
遊離ホノ	レムアル							Ι		Ι																					
デヒ	ド量																														
区分:その (																															
JIS L	JIS L 1041 (アセチルアセトン法)																														
	は実測値																														
																														<u> </u>	<del> </del>
20以	下(0)																														<u> </u>